

HAMMOND POWDERED LEAD

HALO™ Pb-100 POWDERED LEAD TECHNICAL DATA

APPLICATIONS

This material is produced for use in oil & gas drilling lubricants, medical radiological protective devices, and industrial X-ray shielding.

PARTICLE SIZE

US Standard Mesh Size	Typical Value
+50	None
+100	2% Max
+200	5% - 25%
+325	14% - 55%
-325	40% - 90%

PURITY

All Powdered Lead is manufactured with 99.97% pure lead metal. Alternative lead purities are available upon request.

DUST SUPPRESSION

As an option, white oil can be applied to the Powdered Lead to control fugitive dusting.

PACKAGING

Bulk bags: 250 & 500 lbs.
Drums: 400 & 500 lbs.
Pails: 100 & 200 lbs.
Special packaging available upon request

NOTES

This data sheet illustrates typical values for this product. If specific characteristics are required that are different from these values or if custom packaging is required, please contact your area sales representative.

HAMMOND
THE CHANGE CATALYST®

Hammond Lead Products
2901 Carlson Drive, Suite 200
Hammond, IN 46323 USA
Phone: (219) 931-9360
Fax: (219) 931-2140



HAMMONDGLOBAL.COM

©Hammond Group Inc. 2023 · Proprietary Information: Not to be disclosed to a third party without the express written consent of Hammond Group Inc.